





Spec guide




- Deep anti-glare, cutoff angle 40°, with honeycomb accessory
- The light source is OSRAM chip, CRI > 90.
- Stainless steel 316L cover & cord grip with passivation process, suitable for projects close to sea.
- The aluminum lamp housing with CNC process and AkzoNobel coating of double-layer spraying, suitable for projects close to sea.
- Multiple beam angle options, and the illumination is uniform.
- Suitable for facade, landscape and other places.



| Item No. | Power | Beam Angle | lumen(3000K) | Input Voltage |
|----------|-------|----------------------------|-------------------------|---------------|
| VIVA-D1 | 1.5W | 21° 37.4° 15.2*27.5° | 74 lm 52 lm 36 lm | DC24V |

Light distribution curve



| Colour temperature - CRI | IP - IK protection rating | Dimmable | Accessories |
|--------------------------|---------------------------|----------|---|
| 2700K - CRI > 90 | IP67 | Triac |  Aluminum Recessed Sleeve |
| 3000K - CRI > 90 | IK07 | PWM | |
| 3500K - CRI > 90 | | 0~10V | |
| 4000K - CRI > 90 | | DALI | |

Remark:
2*0.5 rubber wire, 1 meter length, includes 4 cm length open wire with wire ferrule